


# Gaja - prisgruppe 3



69008



66005



66004



60999



60003



64005



64004



64010

## Tekniske Data

### Gabriel Gaja

Materiale	100 % Kamgarnull
Bredde	150 cm
Vekt	560 g pr. m <sup>2</sup>
Lysekthet	skala 1-8. max. 8 - BS EN 20105:1993 Method 2
Slitebevegelser (Martindale)	50 000 Slitebevegelser (BS 5690:1991) Martindale
Anvendelsesområde	møbelstolklassifikator 19898 (DB TI/TI)
Flammesikring	Flammehemmende IMO A.652 (16) UK: BS EN 1021 P 1&2 BS 5852 P 2s. 5 USA: FAR 25.853 (B) D: DIN 54342 I&2 - DIN 4102 B2 F: NFP 92503: M2 Flammesikkerheten er avhengig av anvendt skumtype
Rengjøring	Kjemisk rens - P-rens
Fargeavvik	Fargeavvik innenfor kommersielle toleransegrenser kan forekomme
Design	Dorte Bo Bojesen

## Technical Specifications

### Gabriel Gaja

Composition	100 % Worsted wool
Width	150 cm
Weight	560 g pr. m <sup>2</sup>
Light Fastness	skala 1-8. max. 8 - BS EN 20105:1993 Method 2
Abrasion res. (Martindale)	50 000 Rubs (BS 5690:1991) Martindale
Flammability	Flame-retardant IMO A.652 (16) UK: BS EN 1021 P 1&2 BS 5852 P 2s. 5 USA: FAR 25.853 (B) D: DIN 54342 I&2 - DIN 4102 B2 F: NFP 92503: M2 Flammability performance is dependent on foam used.
Maintenance	Dry clean only - P-cleaning
Color Matching	Batch to batch variations in shade may occur within commercial tolerance
Design	Dorte Bo Bojesen